

Practical work on planar contact Integration of Flamant's solution

Vladislav A. Yastrebov

January 22, 2024

Introduction

Let's try to find the stress fields in the vicinity of contact, and displacements on the surface, induced by three specific contact-pressure distributions defined on the interval $x \in [-a, a]$:

1. Uniform pressure (Fig. 1(a)): $p = p_0$
2. Singular at edges pressure (Fig. 1(b)): $p = \frac{p_0}{\sqrt{1 - x^2/a^2}}$
3. "Elliptic" pressure (Fig. 1(c)): $p = p_0 \sqrt{1 - x^2/a^2}$




Figure 1: Pressure distribution on the half-space: (a) uniform, (b) singular at edges, (c) "elliptic" or Hertzian pressure.

To find the stress field and the displacement, we will use the following equations (use numerical integration):

$$\sigma_x(x, y) = -\frac{2y}{\pi} \int_{-b}^a \frac{p(s)(x-s)^2 ds}{((x-s)^2 + y^2)^2}$$

$$\sigma_y(x, y) = -\frac{2y^3}{\pi} \int_{-b}^a \frac{p(s) ds}{((x-s)^2 + y^2)^2}$$

$$\sigma_{xy}(x, y) = -\frac{2y^2}{\pi} \int_{-b}^a \frac{p(s)(x-s) ds}{((x-s)^2 + y^2)^2}$$

$$u_x(x, 0) = -\text{sign}(x) \frac{(1-2\nu)(1+\nu)}{2E} \left[\int_{-b}^x p(s) ds - \int_x^a p(s) ds \right] + C_1$$

$$u_y(x,0) = -\frac{2(1-\nu^2)}{\pi E} \int_{-b}^a p(s) \ln|x-s| ds + C_2$$

Code

You are provided with two simple Python scripts for evaluation of above-mentioned integrals, however, you'll need to substitute correct expression for the integrands.

- To evaluate stresses
`compute_stresses_virgin.py`
- To evaluate displacements
`compute_displacements_virgin.py`

Objectives

1. Find the stress field in a region which extends to $x \in [-2a : 2a]$ and $y \in [-4a : 0]$ for all three pressure distributions mentioned above.
2. Using Hertz's contact formulae, analyze 2D contact between a flat steel substrate ($E = 210$ GPa, $\nu = 0.3$) and a diamond "cylindrical" indenter of radius $R = 10$ mm. Determine the point of the onset of plasticity and the corresponding force F_c using von Mises yield criterion for the yield stress $R = 350$ MPa. The von Mises stress is given by

$$\sigma_{vM} = \sqrt{\frac{3}{2} \underline{\underline{s}} : \underline{\underline{s}}}$$

where the deviator of the stress tensor is given by

$$\underline{\underline{s}} = \underline{\underline{\sigma}} - \frac{1}{3} \text{tr}(\underline{\underline{\sigma}}) \underline{\underline{I}}.$$

Alternatively, the von Mises stress could be found as:

$$\sigma_{vM} = \sqrt{\frac{1}{2} \left[(\sigma_x - \sigma_y)^2 + (\sigma_x - \sigma_z)^2 + (\sigma_y - \sigma_z)^2 + 6(\sigma_{xy}^2 + \sigma_{yz}^2 + \sigma_{xz}^2) \right]}$$

Hint: don't forget about σ_{zz} .

3. Following a similar procedure, find displacements on the top surface $u_x(x,0)$, $u_y(x,0)$ for all three pressure distributions mentioned above.